

CASING, CENTRALIZERS & SCRATCHERS

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)		OD	ID	WT PER FT	GRADE	THREAD	AMT	WT. IN AIR, WT. IN MID		REMARKS
FROM-TO								1000 LBS	1000 LBS	
(S) 0-1600'		9 5/8"	8.845"	32.3#	H-40	STC	1600'	51.7	44.7	
(P) 0-5800'		7"	6.241"	23.0#	K-55	STC	5800'	133.4	113.4	
(P) 5800'-6900'		7"	6.151"	26.0#	K-55	STC	1100'	28.6	24.3	Sand blast & ruff- 600' csg. across pay sections

TYPE OF STRING	CENTRALIZERS		SCRATCHER		OTHER ACCESSORY EQUIPMENT		REMARKS
	INTERVAL		NO. INTERVAL		(SUCH AS DEGASSERS, MUD, CENTRIFUGE		
	NO. FROM-TO	NO. FROM-TO	NO. FROM-TO	NO. FROM-TO	FLOAT COLLARS, ETC. - SPECIFY)		
(S) Surface	(4) 2 ea. on bottom two jts.	(13) One every 15' from shoe to 200' from shoe				Guide shoe & float collar	
	(9) One every 4 jts. to surface						
(P) Production	(4) 2 ea. on bottom two joints	(33) One every 15' from 5950'- 6200' & from 6450'-6700'				Float shoe & float collar	
	(8) One every 3 jts. to 5900'						