

CASING, CENTRALIZERS & SCRATCHERS

LIST TYPE OF STRING BY CODE LETTERS, I.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINDER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)		OD	ID	WT PER FT	GRADE	THREAD	AMT	WT. IN AIR, WT. IN MUD		REMARKS
								1000 LBS	1000 LBS	
(S) 0-1600'	FROM-TO	9 5/8"	8.845"	32.3#	H-40	STC	1600'	51.7	44.7	
		7"	6.241"	23.0#	K-55	STC	5800'	133.4	113.4	
		7"	6.151"	26.0#	K-55	STC	1100'	28.6	24.3	Sand blast & ruff- te 600' csg. across pay sections

TYPE OF STRING	CENTRALIZERS		SCRATCHER	OTHER ACCESSORY EQUIPMENT		REMARKS
	NO. FROM-TO	INTERVAL		NO. INTERVAL	(SUCH AS DEGRASSERS, MUD. CENTRIFUGE FLOAT COLLARS, ETC. - SPECIFY)	

(S) Surface (4) 2 ea. on bottom two jts. (13) One every 15' Guide shoe & float collar
from shoe to
200' from shoe

(9) One every 4 jts.
to surface

(P) Production (4) 2 ea. on bottom two joints (33) One every 15' Float shoe & float collar
from 5950'-
6200' & from
6450'-6700'

(8) One every 3 jts.
to 5900'