

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	F2XX10156			X
RB	General Purpose "U" bolt clamp	UC51046P			
CC	Lightning arrester, 10 KV				
DD	Single phase oil switch, 14.4 KV			MGMW EDISON KIMC-2	
DE	split bolt connector, size req'd			BLACKBURN K SERIES	
FE	grounding specs. see dwg No. ES-11 & ES-1A, Note 3				
GG	35' class 4 creosoted pine pole				
HH	Aluminum deadend Preforms for ACSR, size req'd				
JJ	30' class 6 creosoted pine pole				
KK	OVERHEAD GRND, #4 ACSR - If Req'd - Ref. DWG ES-11, ES-1A - Note 3				
LL	Ground connector, motor			BUKANDY KC-22	X
NM	600 V. secondary lightning arrester single phase				
NN	Greenfield type LF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
OO	req'd size LB fitting & cover & gasket				
PP	transformer tank grounding terminal	GW5-75			
QQ	Bird Guards (insulating boots on transformer bushings)			URS-1104-1102-25	

DATE:	12-27-71	TITLE:	DESCRIPTION MATERIAL
DRAWN BY:	E. WINTER	CONOCO HOBBS DIVISIC	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE:	NONE	JOB:	REC SPECS
		DRAWING NO:	ES-1
		SHEET 2 OF 3	