

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
a	double upset bolt s/sq. nut, round washer, and cotter key on short end, sq. nut and WF locknut on long end, 15 1/8" long (or length required.) wet process porcelain secondary spool insulator,	1828			
b	3", brown glaze required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. DWG BS-1B Note: provide clamp and ground conduit parallel groove clamp, size req'd		2101		
d				BURNDY SERIES "UC"	
e					
f	secondary insulator clevis for 4" insulator	6510			
g	5/8" thimble nut				
h	5/8" x 12" (or length req'd) straight thimble bolt w/sq. nut	5512		ALUMA FORM 6M3-6	X
j	transformer cluster mount bracket (small)			ALUMA FORM 15M3-6	X
l	transformer cluster mount bracket (large)				
m	req'd size raintight disconnect & fuses, 3-phase, 600 V. Ref. DWG No. ES-1B				
n	16" cross plate anchor (or size req'd)	X-16 88135			
q	8-way expanding anchor (size req'd)		20101		
r	4" brown glaze wet process porcelain secondary spool insulator				
u	5/8" x 7' thimble anchor rod w/nut (use twineye if req'd - Chance No. 5347)	5317 (NUT 55006P)			
ae	3/8" high strength guy strand (10,800 lb.)				
bb	preformed guy rip for 3/8" guy strand	5010			
dd	5/8" x 10" angle thimble bolt w/nut	6813 1/2			X
ee	3"x3"x1/4"x11/16" hole curved washer				
ff	6" - guy clamp w/3-1/2" bolts				
gx	medium size strain insulator	6454			
hh	serving sleeve for 3/8" guy strand	7887			X
jj	3/16" x 2-1/2" x 7" lift plate				
mm	pole bottom ground plate (may use butt-wrap if desired)				
nn	Ground connection (See DWG. ES-12)				
qq	wet process porcelain secondary spool insulator,				
rr	3" - white glaze				
tt	4" - white glaze				

DATE:	12-27-71	TITLE:	DESCRIPTION MATERIALS
DRAWN BY:	E. WINTER	CONOCO HOBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE:	NONE	JOB:	ELEC SPECS
		DRAWING NO.:	ES-1
			SHEET 3 OF 5