

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)		DRIIFT		WT PER FT	GRADE	THREAD	AMT	WT. IN AIR, WT. IN MUD		REMARKS
FROM-TO	OD	ID						1000 LBS	1000 LBS	
(S) 0'-1650'	8-5/8"	7.972"		24#	K-55	STC	1650'	39.6		
(P) 0'-6420'	5-1/2"	4.825"		15.5#	K-55	LTC	6420'	99.5		Sandblast bottom 500'
										D.V. Tool @ 4000'

TYPE OF STRING	CENTRALIZERS		SCRATCHER		OTHER ACCESSORY EQUIPMENT		REMARKS
	INTERVAL	NO. FROM-TO	INTERVAL	NO. FROM-TO	(SUCH AS DEGASSERS, MUD, CENTRIFUGE	FLOAT COLLARS, ETC. - SPECIFY)	
Surface	(17) 0'-1650'		(15' spacing)	NONE	Guide shoe and float collar	100' spacing for centralizers	
Production	(2) 1550'-1650'	(27) 6020'-6420'			Float shoe, float collar, D.V. Tool, and 2 metal petal baskets (below D.V. Tool)	Centralizers: 2 just above 8- shoe, remainder one per joint.	