

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SALE PRICE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCC-HOBBS
1-R. J. STARRAK-TULSA
1-A. B. CARY-MIDLAND
1-FILE
1-BH, FIELD CLK
1-OH, FOREMAN
1-PJB, ENGR.
1-AMERADA HESS, TULSA

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
LG-1103	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER	7. Unit Agreement Name
2. Name of Operator Getty Oil Company	8. Form or Lease Name Getty "1" State
3. Address of Operator P. O. Box 730, Hobbs, NM 88240	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>22S</u> RANGE <u>34E</u> NMPM.	10. Field and Pool, or Wildcat Grama Ridge
15. Elevation (Show whether DF, RT, GR, etc.) 3607 GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-5-79 Drilled 8 1/2" hole to 11,075'. Ran 260 jts. 7" OD 26# S-95 and N-80 8rd LT&C csg. (11,051') and set at 11,075', float shoe at 11,073-11,075', float collar at 10,982-10,984', and DV tool at 8028-8031'.

Howco cemented in two stages:

First Stage: 200 sxs Howco Lite Water with 3# gilsonite, 1/4# flocele, and .6% Halad 22/sx; tailed in with 300 sxs Class "H" cement with 3# salt and .8% Halad 22/sx. Circulated 175 sxs cement.

Second Stage: 1000 sxs Howco Lite Water with 3# gilsonite, 1/4# flocele, .6% Halad 22/sx; tailed in with 200 sxs Class "H" cement with 3# salt and .8% Halad 22/sx. Circulated 150 sxs cement.

Total cement - 1700 sxs. Waiting on cement.

9-7-79 Drilled DV tool (10' cement above float collar at 60' above and 88' cement in shoe jt.) Tested DV tool at 3000# OK. Tested formation at 3000# OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Dale R. Crockett</u>	TITLE <u>Area Superintendent</u>	DATE <u>9-26-79</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dist. 1. Supv.</u>	DATE <u>SEP 27 1979</u>
CONDITIONS OF APPROVAL, IF ANY		