

ITEM	DESCRIPTION	A. B. CHANGE NO.	JESLYN NO.	OTHER MERS. NO.	NO. SUB.
A	35' class 6 cross-rod, plus pole				
B	3 1/2" x 1/2" x 8' treated cross-rod				
C	high quality wet process porcelain pin insulator				
D	5/8" x 50' forged steel pin w/d. washer, nut, & locknut	330	753		
E	5/8" x 12" cast-iron lock nut (or length req'd)	340			
F	2 1/2" x 2 1/4" x 3/16" x 11/16" hole sq. washer	600			
G	5/8" x 12" lock nut	350			
H	1 1/2" x 1 1/4" x 28" flat cross-arm brace	220			
I	1/2" x 4" F. better plate for screw	600			
J	3/8" x 4 1/2" carriage bolt w/ nut	600			
K	1/8" x 4 1/2" carriage bolt w/ nut	350			
L	Preformed Aluminum Alloy Arched Rod, size req'd				
M	Preformed Aluminum Alloy Arched Rod, size req'd				
N	Preformed Aluminum Alloy Arched Rod, size req'd				
O	Preformed Aluminum Alloy Arched Rod, size req'd				
P	Preformed Aluminum Alloy Arched Rod, size req'd				
Q	Preformed Aluminum Alloy Arched Rod, size req'd				
R	Preformed Aluminum Alloy Arched Rod, size req'd				
S	Preformed Aluminum Alloy Arched Rod, size req'd				
T	Preformed Aluminum Alloy Arched Rod, size req'd				
U	Preformed Aluminum Alloy Arched Rod, size req'd				
V	Preformed Aluminum Alloy Arched Rod, size req'd				
W	Preformed Aluminum Alloy Arched Rod, size req'd				
X	Preformed Aluminum Alloy Arched Rod, size req'd				
Y	Preformed Aluminum Alloy Arched Rod, size req'd				
Z	Preformed Aluminum Alloy Arched Rod, size req'd				

DATE: 12-27-71	TITLE: DESCRIPTION MATERIALS
DRAWN BY: J. WATKINS	CONOCO
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	
SCALE: NONE	PRODUCTION DEPT: HOBBS DIVISION
	JOB: ES-1
	SHEET 1