

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator  
Chevron U.S.A. Inc.

Address of Operator  
P.O. Box 670 Hobbs, NM 88240

Location of Well

UNIT LETTER G 2530 FEET FROM THE North LINE AND 2430 FEET FROM THE East LINE, SECTION 29 TOWNSHIP 21S RANGE 37E NMPM.

7. Unit Agreement Name  
Central Drinkard Unit

8. Farm or Lease Name

9. Well No.  
427

10. Field and Pool, or Wildcat  
Drinkard

15. Elevation (Show whether DF, RT, GR, etc.)

3447

12. County  
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

ORM REMEDIAL WORK ☐  
PERMANENTLY ABANDON ☐  
OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER sqz, dpn, acdz ☒

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/13/88 thru 7/25/88

POOH w/production equipment. Drill scale f/6382 to 6496. Circ. wellbore. Set cmt rtnr at 6311. Load wellbore w/ CBW. Mix and pump 250sx Class C. Hesitate 18 min. Reverse cmt. WOC. TAG cmt at 5520'. Drill cmt to 6300'. Circ wellbore clean. Drill cmt and retainer. Fell out of cement totally at 6450'. Set retainer at 6284'. Mix and pump 200sx Class C, displace w.FW. WOC 24 hrs. Tag cmt at 6271'. Cmt rtnr at 6284'. Drilled cmt f/ 6271' to 6422'. Circ. clean. Swab. Drilled f/6496' to 6504'. Drilled hard cmt and junk. Circ. clean. Drilled cmt f/6504' to 6534. Circ. clean. Drilled 6612', Circ. clean. Log w/CNL/GR/CCL. Pump 1000 gal. 15% NEFE HCL. Swab well. RIH w/ 2 3/8" J-55, 4.7# EUE to 6576'. SN at 6539. TAC at 6347'. Space out clamp, hand rods on beam. Release rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

M. E. Atkins

TITLE Staff Drilling Engr.

DATE August 4, 1988

Eddie W. Seay

Oil & Gas Inspector

TITLE

DATE

AUG 09 '88

CONDITIONS OF APPROVAL, IF ANY: