

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-025-26448
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: CENTRAL DRINKARD UNIT
8. Well No. 429
9. Pool name or Wildcat DRINKARD
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3460'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other
2. Name of Operator Chevron U.S.A. Inc.
3. Address of Operator P.O. Box 1150 Midland, TX 79702
4. Well Location Unit Letter G : 2500 feet from the NORTH line and 1540 feet from the EAST line Section 32 Township 21S Range 37E NMPM County LEA

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3460'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐

OTHER: **DEEPEMED**

☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

POH W/PROD EQPT. SQZD 6319'-6504' W/100 SX CMT @ 3000 PSI. PRESS TO 1000 PSI-OK.
DO CMT TO 6506'; WASHED TO 6536'. DRILLED TO 6665'. CIRC HOLE CLEAN. LOGGED.
ACZD W/4000 GALS 15%. SWABBED. ACZD W/8000 GALS 20% EMULSIFIED ACID & 4500 GALS
20% HCL. SWABBED. RIH W/TBG, PUMP & RODS; TBG @ 6590'. RETURNED WELL TO PRODUCTION.

WORK PERFORMED 12/8/00 - 1/5/01

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. K. Ripley TITLE REGULATORY O.A. DATE 2/7/01

Type or print name J. K. RIPLEY Telephone No. (915) 687-7148

(This space for State use)

APPROVED BY J. K. Ripley TITLE REGULATORY O.A. DATE 2/7/01

Conditions of approval, if any: