

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-26505
Indicate Type of Lease STATE ☒ FEE ☐
State Oil & Gas Lease No. B-935
Lease Name or Unit Agreement Name New Mexico "DU" State
Well No. 1
Pool name or Wildcat East Grama Ridge Strawn (Gas)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐	
Name of Operator John H. Hendrix Corporation	
Address of Operator P. O. Box 3040, Midland, TX 79702-3040	
Well Location Unit Letter <u>F</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>1650</u> Feet From The <u>West</u> Line Section <u>12</u> Township <u>22S</u> Range <u>34E</u> NMPM <u>Lea</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3544' GR	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/13/00 Set 4-1/2" CIBP @ 11,997'. Dumped 38' cement on top of CIBP at 11,997'. Tagged cement at 11,958'. Set 4-1/2" CIBP at 11,780'. (Perfs. 11,821 - 11,912'). Dumped 38' of cement on top of CIBP at 11,780'. Monitored by E. L. Gonzales w/ NMOCD.

12/14/00 RIH w/ 2-3/8" tbg. to 11,700'. Circ. 10# brine wtr. w/ 25#/bbl. salt gel fr. 11,700 - 6650'. RIH & tagged cement to 11,745'. Set 7-5/8" CIBP at 10,800'. (Liner top at 10,898'. Capped CIBP at 10,800' w/ 52' cement. Monitored by E. L. Gonzales.

12/15/00 Tagged cement at 10,740'. Set tubing at 8195'. Finished circ. hole w/ P&A mud, 280 bbls. w/ 25# bbls. gel in 10# brine water.

12/17/00 Spotted 50 sx. Class H plug fr. 824 - 7973'. Spotted 50 sx. Class C plug w/ 2% CaCl2 fr. 5751 - 5480'. Tagged cement at 5504'. Set 50 sx. Class C plug 1609 - 1361'. Perf. 7-5/8" csg. at 450'. Cemented down 7-5/8" csg. up 7-5/8" x 10-3/4" annulus w/ 200 sx. Class C. Circ. 40 sx.

12/18/00 Installed dry hole marker.

12/20/00 Backfilled working pit, cleaned location - Well P&A'd.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie H. Westbrook TITLE Vice President DATE 01-08-01

TYPE OR PRINT NAME Ronnie H. Westbrook

TELEPHONE NO.

(This space for State Use)

Harry W. Wink
APPROVED BY WINK

COPIES OF APPROVAL

Approved as to plugging of the Well Bore
Liability under bond is retained until
surface restoration is completed.

EEB 25 2003

GWW

