

ITEM	DESCRIPTION	A. B. QUANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
A	35' class 6, creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	high density set process porcelain pin insulator				
D	5/8" x 5" Forged steel pin w/aq. washer, nut, & locknut	881			
E	5/8" x 12" machine bolt w/ nut (or length req'd)	8812			
F	2 1/2" x 2 1/2" x 3/16" x 11/16" hole sq. washer	6813			
G	5/8" HF locknut	5812			
H	1/4" x 1 1/4" x 28" flat crossarm brace	7126			
J	1/2" x 4" E2 Fetter Drive Top Screw	508254			
K	3/8" x 4 1/2" carriage bolt w/ Nut	8634 1/2			
L	3/8" HF Locknut	3510			
M	Preformed Aluminum Alloy Armor Rods, size req'd				
N	tie wire 76 strong alum. alloy				
O	Epoxy Insulator (Extension Link)			NEARNEY-23102560	X
P	35' class 5 creosoted pine pole				
R	Aluminum double tab Squeeze on Connector for ACSP, Aluminum, or Copper-size req'd			NEARNEY SERIES "SI"	X
S	5' Suspension Insulator	44200			
T	5/8" Standard Oval Eye Nut	6502			
U	Primary Dead End Clamp		43050		
W	5/8" x 18" (or length req'd) Double Arming Bolt w/4 sq. nuts	8868			
X	guying detail - see dwg No. ES-10 for spec.				
Y	Hot Line Clamp				
Z	Squeeze on basket, size required	5152066P		NEARNEY	X

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO	
DESIGN BY:		PRODUCTION DEPT.	
CHECKED BY:		JOB: MORRIS DIVISION	
APPROVED BY:		DRAWING NO: ES-1	
SCALE: NONE		ELEC SPECS SHEET 10-3	