

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
AA	Primary cutout - 100 amp, 15 kv, 16000 amp int. cap.	E24410156			X
AB	General purpose 1/2" bolt clamp	UE 31028P			
AC	Lightening arrester, 10 kv				
AD	Single phase oil switch, 14.4 kv				
AE	Split bolt connector, size req'd				
AF	Grounding spere. see det No. ES-11 & ES-1A, Note 3				
AG	3" class 4 creosoted pine pole				
AH	Aluminum deadend fitting for A-SB, size req'd				
AI	30" class 6 creosoted pine pole				
AK	OVERHEAD GRN, 1/4" ACSR - 1f Req'd - Ref. Dwg ES-11, ES-1A - Note 3				
AL	Ground connector, motor				
AM	600 V. secondary lightening arrester single phase				
AN	Greenfield Type EF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
AO	req'd size 1 1/2" fitting & cover & gasket				
AP	transformer tank bonding terminal	GWD-15			
AQ	Bird Guards (insulating boots on transformer bushings)				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIAL	
DRAWN BY: E. HUNTER		CONOCO	
DESIGN BY:		PRODUCTION DEPT. HOBBS DIVISIO	
CHECKED BY:		JOB: DRAWING NO.	
APPROVED BY:		FLEC-SPECS ES-1	
SCALE: NONE		SHEET 2	