

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
a	double upset bolt w/eq. nut, round washer, and cotter key on short end, eq. nut and MF locknut on long end, 15 1/8" long (for length required.)	742B			
b	wet process porcelain secondary spool insulator, 3" brown glaze		1101		
d	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Div. US-11 Note: provide clamp and ground conduit				
e	parallel groove clamp, size req'd				
f	secondary insulator clevis for 4" insulator				
g	5/8" thimble nut	5510			
h	5/8" x 12" (or length req'd) straight thimbleye bolt w/eq. nut	5512			
j	transformer cluster mount bracket (small)				
k	transformer cluster mount bracket (large)				
m	req'd size raintight disconnect & fuses, 3-phase, 600 V., Ref. Div. No. 55-11				
n	16" cross plate anchor (or size req'd)	X-16			
q	8-way expanding anchor (size req'd)	BB135			
t	4" brown glaze wet process porcelain secondary spool insulator		1101		
u	5/8" x 7" thimbleye anchor rod w/nut (use twineye if req'd - Change No. 5347)	5317 (NOT 5300P)			
va	3/8" high strength guy strand (10,800 lb.)				
bb	preferred guy grip for 3/8" guy strand				
dd	5/8" x 10" angle thimbleye bolt w/nut	5210			
ee	3"x3"x1/2"x1/16" hole curved washer	6B23 1/2			
ff	6" - guy clamp w/3-1/2" bolts				
gg	medium size strain insulator				
hh	serving sleeve for 3/8" guy strand	6454			
ii	3/16" x 2-1/2" x 7" lift plate	7887			
nn	pole bottom ground plate (may use butt-wrapp if desired)				
qq	Ground connection (See Div. 55-11)				
rr	wet process porcelain secondary spool insulator, 3" - white glaze				
tt	wet process porcelain secondary spool insulator, 4" - white glaze				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO	
DESIGN BY:		PRODUCTION DEPT.	
CHECKED BY:		HOBBS DIV.	
APPROVED BY:		DRAWING NO.	
SCALE: NONE		ELEC. SPECS.	
		ES-1	
		SHEET 1	