

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
A	35' class 6, ringed pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	high density wet process porcelain pin insulator				
D	5/8" x 5" forged steel pin w/alt. washer, nut, & locknut	88/	763		
E	5/8" x 12" machine bolt w/ nut (or length req'd)	3472			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole sq. washer	6873			
G	5/8" NF locknut	3512			
H	1/4" x 1 1/4" x 5/8" flat crossarm brace	7721			
I	1/2" x 4" E2 feather drive lag screw	508754			
J	3/8" x 4 1/2" carriage bolt w/ nut	663421			
K	3/8" NF locknut	3510			
L	Preformed Aluminum Alloy Armor Rods, size req'd				
M	tie wire #6 alloy alum. alloy				
N	Ency Insulator (extension link)				
O	35' class 5, crossarm pine pole				
P	Aluminum double tab squeeze on connector				
Q	for ACSR, Aluminum, or Copper-size req'd				
R	6" Suspension Insulator	6400			
S	5/8" Standard Oval Eye Nut	4502			
T	Primary Dead End Clamp				
U	5/8" x 18" (or length req'd) Double Arming Bolt	8868	44250		
V	w/4 sq. nuts				
W	Buyline detail - see tag No. ES-10 for specs.				
X	Hot Line Clamp				
Y	Squeeze on basket, size required	515206P			
Z					

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO	
DESIGN BY:		PRODUCTION DEPT.	
CHECKED BY:		JOB: HOBBS DIVISION	
APPROVED BY:		DRAWING NO: ES-1	
SCALE: NONE		ELEC SPECS	
		SHEET 1 OF 3	