

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	CT. IER. MFRS. NO.	NO. SUP.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	FLXX/1015G			X
BB	General Purpose 100 bolt clamp	CC/51045B			
CC	Lightening arrester, 10 KV				
DD	Single phase oil switch, 1A, 4 KV				
EE	split bolt connector, size req'd				
FF	Grounding device, see spec. for ES-11 & ES-1A, Note 3				
GG	35' class 4 steel pole				
HH	Aluminum dendend Preforms for ACSR, size req'd				
II	30' class 6 steel pole				
KK	OVERHEAD CRND, 04 ACSR - 14 Ref. Dag ES-11.				
LL	ES-1A - Note 3				
MM	ground connector, motor				
NN	600 V. secondary lightening arrester, single phase				
OO	Greenfield Type FF liquid-tight flexible steel				
PP	conduit, size req'd, w/ necessary liquid-tight				
QQ	connectors.				
RR	req'd size 1/2 fitting & cover & packet				
SS	transformer tank grounding terminal				
TT	Bird Guards (insulating boots on transformer bushings)				
UU					
VV					
WW					
XX					
YY					
ZZ					

DATE: 12-27-71		TITLE: DESCRIPTION MATERIAL	
DRAWN BY: E. WINTER		CONOCO HOBBS DIVISION PRODUCTION DEPT. JOB: ES-1 DRAWING NO: 1 SHEET 1 OF 3	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		FLEC-SPEC3	