

ITEM	DESCRIPTION	A. B. QUANCE NO.	JOSLYN NO.	OTHER MERS. NO.	NO. SUB.
a	double upset bolt w/aq. nut, round washer, and cotter key on short end, an. nut and HF locknut on long end, 15 1/8" long (or length required.)	7428			
b	wet process porcelain secondary spool insulator, 3", brown glaze		4101		
d	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES 10 Note: provide clamp and ground conduit				
e	parallel groove clamp, size req'd				
f	secondary insulator clevis for 4" insulator				
g	5/8" x 12" (or length req'd) straight thimbleye bolt w/aq. nut	6310			
h	transformer cluster mount bracket (small)	5512			
i	transformer cluster mount bracket (small)				
l	transformer cluster mount bracket (large)				
m	req'd size raintight disconnect & fuses, 3-phase, 600 V., Ref. Dwg No. ES-10				
n	16" cross plate anchor (or size req'd)	X-16			
o	8-way expanding anchor (size req'd)	80135			
t	4" brown glaze wet process porcelain secondary spool insulator		4101		
u	5/8" x 7" thimbleye anchor rod w/nut (use twineye if req'd - Chance No. 5347)	5317 (NUT 55006P)			
ee	3/8" high strength guy strand (10,800 lb.)				
bb	preferred guy grip for 3/8" guy strand				
dd	5/8" x 10" angle thimbleye bolt w/nut	5010			
ee	3"x3 1/4"x11 1/16" hole curved washer	6033 1/2			
ff	6" - guy clamp w/3-1/2" bolts				
gg	medium size strain insulator				
hh	serving sleeve for 3/8" guy strand	6344			
jj	3/16" x 2-1/2" x 7" 111c plate	7887			
nn	pole bottom ground plate (may use butt-wrap if desired)				
qq	Ground connection (See Dwg. ES-12)				
rr	wet process porcelain secondary spool insulator, 3" - white glaze				
tt	wet process porcelain secondary spool insulator, 4" - white glaze				

TITLE: DESCRIPTION MATERIALS	
DATE: 12-27-71	
DRAWN BY: E. WINTER	
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	
SCALE: NONE	

CONOCO	PRODUCTION DEPT.	HOBBS DIST.
	JOB:	DRAWING NO:
	ELEC SPECS	ES-1
		SHEET 3 OF