DISTRIBUTION		Supersedes Old
013	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
ANTA FE	NEW WEXICO OIL CONSERVATION COMMISSION	
ILE		Sa. Indicate Type of Lease
.s.G.5.		State X Foo S. State Cil & Gas Lease No.
AND OFFICE		S. State Cit & Clas Lease No.
PERATOR		mmmmmm
	UNDRY NOTICES AND REPORTS ON WELLS	
100 HOT UTE THIS FORSE !	UNDRY NOTICES AND REPORTS ON WELLS DIFFERENT RESERVOIR.	7. Unit Agreement forme
OIL CAS WELL	X other	8. Farm or Lease Name
lame of Cyerator		State GC
Amoco Production	Company	9, Well 1:5.
	bbs NM 88240	10, Field and Pool, or Wildcat
P. O. Box 68, Ho	DOS. NO COLIC	
UNIT LETTER	. 660 FEET FROM THE SOUTH LINE AND 1980 FEET FR	
East Line	., SECTION 7 TOWNSHIP 22-S RANGE 35-E NM	PM.
	15. Flevation (Show whether DF, RT, GR, etc.)	12. County
	3603.0 GL	Lea
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING DPNS. CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER	ALTERING CASING PLUG AND ABANDONMENT
17. Describe Fro; osed or Com	pletes Operations (Clearly state all pertinent details, and give pertinent dates, incit	ding estimated date of starting any propo
Drilled to a TD	of 5700' and ran 10-3/4" 51# casing set at 5700'. nt and 200 sx Class C cement. Plugged down 3:45 A. hrs. Tested casing with 1000# for 30 min. Test Ol	Cemented with 4200 sx
Drilled to a TD Halco Lite ceme 90 sx. WOC 18	of 5700' and ran 10-3/4" 51# casing set at 5700'. nt and 200 sx CTass C cement. Plugged down 3:45 A hrs. Tested casing with 1000# for 30 min. Test O	Cemented with 4200 sx
Drilled to a TD Halco Lite ceme 90 sx. WOC 18	of 5700' and ran 10-3/4" 51# casing set at 5700'. nt and 200 sx CTass C cement. Plugged down 3:45 A hrs. Tested casing with 1000# for 30 min. Test O	Cemented with 4200 sx
Drilled to a TD Halco Lite ceme 90 sx. WOC 18	of 5700' and ran 10-3/4" 51# casing set at 5700'. nt and 200 sx CTass C cement. Plugged down 3:45 A. hrs. Tested casing with 1000# for 30 min. Test Ol	Cemented with 4200 sx
Drilled to a TD Halco Lite ceme 90 sx. WOC 18	of 5700' and ran 10-3/4" 51# casing set at 5700'. nt and 200 sx CTass C cement. Plugged down 3:45 A. hrs. Tested casing with 1000# for 30 min. Test Ol	Cemented with 4200 sx
Drilled to a TD Halco Lite ceme 90 sx. WOC 18 and resumed dri	of 5700' and ran 10-3/4" 51# casing set at 5700'. nt and 200 sx CTass C cement. Plugged down 3:45 A. hrs. Tested casing with 1000# for 30 min. Test Of	Cemented with 4200 sx
Drilled to a TD Halco Lite ceme 90 sx. WOC 18 and resumed dri	of 5700' and ran 10-3/4" 51# casing set at 5700'. nt and 200 sx CTass C cement. Plugged down 3:45 A. hrs. Tested casing with 1000# for 30 min. Test Of	Cemented with 4200 sx
Drilled to a TD Halco Lite ceme 90 sx. WOC 18 and resumed dri	of 5700' and ran 10-3/4" 51# casing set at 5700'. nt and 200 sx CTass C cement. Plugged down 3:45 A. hrs. Tested casing with 1000# for 30 min. Test Ol	Cemented with 4200 sx .M. 1-17-80. Circulated <. Reduced hole to 9-1/2'

Orig. Signed by

Les Clements

Oil & Gas Insp.

CONDITIONS OF APPROVAL, IF ANY:

0+4 NMOCD-H 1-HOIL 1-SUSD. 1-BD