

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER MERS. NO.	NO. SUB.
A	35' class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	high density set process porcelain pin insulator				
D	5/8" x 5" forged steel pin w/eq. washer, nut, & locknut	881	263		
E	3/8" x 12" machine bolt w/ nut (or length req'd)	881/2			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole sq. washer	681/3			
G	5/8" NF locknut	35/2			
H	1 1/4" x 1 1/4" x 28" flat crossarm brace	7128			
J	1 1/2" x 4" E2 Fetter Drive Lag Screw	508754			
K	3/8" x 4 1/2" carriage bolt w/ Nut	8634 1/2			
L	3/8" NF locknut	35/0			
M	Preformed Aluminum Alloy Armor Rods, size req'd				
N	tie wire #6 strong alum. alloy				
O	Flow insulator (Extension Link)				
P	35' class 5 creosoted pine pole				
R	Aluminum double tab Squeeze on Connector for ACSR, Aluminum, or Copper-size req'd				
S	6" Suspension Insulator	66200			
T	5/8" Standard Oval Eye Nut	6502			
U	Primary Dead End Clamp				
W	5/8" x 18" (or length req'd) Double Arming Bolt w/6 sq. nuts	8868	24050		
X	Buying detail - see spec No. ES-10 for spec.				
Y	Hot Line Clamp				
Z	Squeeze on basket, size required	51520AGP			
				KEARNEY	X

DATE: 12-27-71	TITLE: DESCRIPTION MATERIALS
DRAWN BY: K. WINTER	
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	
SCALE: NONE	PRODUCTION DEPT. HOBBS DIVISION JOB: DRAWING NO. ES-1 ELEC. SPEC. SHEET 1 OF 3