

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	F2XX1015G			X
BB	General Purpose "U" bolt clamp	UL510AGP			
CC	Lightening arrester, 10 KV				
DD	Single phase oil switch, 14.4 KV				
DE	Split bolt connector, size req'd				
FE	Grounding specs. see dsg No. ES-11 & ES-1A, Note 3				
GG	35' class 4 creosoted pine pole				
HH	Aluminum deadend Preforms for ACSB, size req'd				
JJ	30' class 6 creosoted pine pole				
KK	OVERHEAD GRND, 44 ACSB - 1/2 Req'd - Ref. Dsg ES-11, ES-1A - Note 3				
LL	Ground connector, motor				
MM	600 V. secondary lightening arrester single phase				
NN	Greenfield Type FF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
OO	Req'd size JB fitting & cover & gasket				
PP	Transformer tank grounding terminal				
QQ	Bird Guards (insulating boots on transformer bushings)	GW3-15			

DATE: 12-27-71	TITLE: DESCRIPTION MATERIAL
DRAWN BY: E. WINTER	CONOCO
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	PRODUCTION DEPT: HOBBS' DIVISION
SCALE: NONE	JOB: DRAWING NO. ES-11
	ELEC. SPECS
	SHEET 2 OF 3