

ITEM	DESCRIPTION	A. B. QUANT. NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
A	35' class 6 creoproted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	High density wet process porcelain pin insulator		163		
D	5/8" x 5" Forged steel pin w/eq. washer, nut, & locknut				
E	5/8" x 12" machine bolt w/ nut (or length req'd)				
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole eq. washer				
G	3/8" HF Locknut				
H	1/4" x 1 1/4" x 28" flat crossarm brace				
J	1/2" x 4" ez felter drive Log Screw				
K	3/8" x 4 1/2" Carriage bolt w/ Nut				
L	3/8" HF Locknut				
M	Preformed Aluminum Alloy Armor Rods, size req'd				
N	tie wire #6 strong alum. alloy				
O	Epoxy Insulator (Extension Link)				
P	35' class 5 creoproted pine pole				
R	Aluminum double tab Squeeze on Connector for A/SR, Aluminum, or Copper-size req'd				
S	6" Suspension Insulator				
T	5/8" Standard Oval Eye Nut				
U	Primary Dead End Clamp				
V	5/8" x 18" (or length req'd) Double Arming Bolt w/4 sq. nuts				
X	Buying detail - see dwg No. ES-10 for spec.				
Y	Hot Line Clamp				
Z	Squeeze on basket, size required				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIAL	
DRAWN BY: J. WINTER		CONOCO PRODUCTION DEPT. HOBBS DIVISION CHECKED BY: DRAWING NO: APPROVED BY: JOB: SCALE: NONE ELEC SPECS ES-1 SHEET 3	