

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
AA	Primary Cutout - 100 amp, 15 kv, 16000 amp int. cap.	FLX1015G			X
BB	General Purpose 1/2" bolt clamp	UC510AGP			
CC	Lightning arrester, 10 kv				
DD	Single phase oil switch, 14.4 kv			W644100014422	
EE	split bolt connector, size req'd			W644100014422	
FF	Grounding specs. see det. No. ES-11 & ES-1A, Note 3				
GG	35' class 4 creosoted pine pole				
HH	Aluminum deadend Perform for ACSR, size req'd				
II	30' class 6 creosoted pine pole				
KK	OVERHEAD GRND, #6 ACSR - If Req'd - Ref. det ES-11. FS-1A - Note 3				
LL	Ground connector, motor				
MM	600 V. secondary lightning arrester single phase			W644100014422	X
NN	Greenfield Type EF liquid-tight flexible steel conduct, size req'd, w/ necessary liquid-tight connectors.				
OO	req'd size LB fitting & cover & gasket				
PP	transformer tank grounding terminal	QWS-15			
QQ	Bl'd Guards (insulating hoods on transformer bushings)				

DATE: 12-27-71	TITLE: DESCRIPTION MATERIAL	
DRAWN BY: E. WINTER		
DESIGN BY:		
CHECKED BY:		
APPROVED BY:		
SCALE: NONE	JOB: FILED SPECS	DRAWING NO: ES-1
	SHEET 2 OF 3	
	CONOCO HORBS DIVISION	