

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSELYN NO.	OTHER MFRS. NO.	NO. SUB.
A	35' class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	High density wet process porcelain pin insulator		663		
D	5/8" x 5" forged steel pin w/eq. washer, nut, & locknut	881			
E	5/8" x 12" machine bolt w/ nut (or length req'd)	6612			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole sq. washer	6812			
G	5/8" NF locknut	3512			
H	1/4" x 1 1/4" x 28" flat crossarm brace	7128			
I	1/2" x 4" E2 Fetter Drive Lag Screw	508754			
J	3/8" x 4 1/2" carriage bolt w/ Nut	863412			
K	3/8" NF locknut	3510			
L	Preformed Aluminum Alloy A nut Rods, size req'd				
M	tie wire 46 strong Alum. alloy			LEANNEX-3205560	X
N	Epoxy Insulator (Extension Link)				
O	35' class 5 creosoted pine pole				
P	Aluminum double tab Squeeze on Connector for ACSR, Aluminum, or Copper-size req'd			KLARNEY SERIES "B"	X
R	6" Suspension Insulator	64200			
S	5/8" Standard Oval Eye Nut	6502			
T	Primary Dead End Clamp		69250		
U	5/8" x 18" (or length req'd) Double Arming Bolt	8868			
V	W/4 sq. nuts				
X	Buying detail - see dog No. ES-10 for specs.				
Y	Hot Line Clamp				
Z	Squeeze on basket, size required	51820062		KLARNEY	X

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: J. WINTER		CONOCO HOBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB:	ES-1
		SHEET 1 OF 3	