

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
MA	Primary Cutout - 100 amp, 15 kv, 16000 amp int. cap.	F2X10/56			X
MB	General Purpose "H" bolt clamp	UC510AGP			
MC	Lightening arrester, 10 kv				
MD	Single phase oil switch, 16 & kv				
ME	Split bolt connector, size req'd				
MF	Grounding spec. see det. No. ES-11 & ES-1A, Note 3				
MG	35' class 4 creosoted pine pole				
MH	Aluminum deadend Preforms for ACSR, size req'd				
MI	30' class 6 creosoted pine pole				
MJ	OVERHEAD GRND, #4 ACSR - 16 Req'd - Ref. Det. ES-11,				
MK	ES-1A - Note 3				
ML	Ground connector, motor				
MM	600 V. secondary lightning arrester single phase				
MN	Greenfield type of liquid-tight flexible steel				
MO	conduit, size req'd, w/ necessary liquid-tight				
MP	req'd size lb fitting & cover & gasket				
MQ	transformer tank grounding terminal				
MR	Bird Guards (insulating boots on transformer bushings)				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIAL	
DRAWN BY: E. WALTER		CONOCO HOBBS PRODUCTION DEPT. DRAWING NO. 11510N	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		REC SPECS SHEET 2 OF 3	