

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
a	double upset bolt w/eq. nut, round washer, and cotter key on short end, eq. nut and HP locknut on long end, 15 1/8" long (or length required.)	1/828			
b	wet process porcelain secondary spool insulator, 3", brown glaze		1/101		
d	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. DWG ES-18 Note: provide clamp and ground conduit parallel groove clamp, size req'd			BURNDY TITLES "UC"	
e	secondary insulator clevis for 4" insulator	6510			
f	3/8" thimble nut	5512			
g	3/8" x 12" (or length req'd) straight thimble bolt w/eq. nut			ALUMALLOY BM3-6	X
j	transformer cluster mount bracket (small)			ALUMALLOY BM3-6	X
l	transformer cluster mount bracket (large)				
m	req'd size raintight disconnect & fuses, 3-phase, 600 V., Ref. DWG No. ES-18	X-16			
n	16" cross plate anchor (or size req'd)	68135			
q	8-way expanding anchor (size req'd)		10101		
z	4" brown glaze wet process porcelain secondary spool insulator	5317 (WUT 55006P)			
u	5/8" x 7" thimble anchor rod w/nut (use twineye if req'd - Chance No. 5347)				
aa	3/8" high strength guy strand (10,800 lb.)				
bb	preferred guy clip for 3/8" guy strand	5010			
dd	3/8" x 10" angle thimble bolt w/nut	6813 1/2			X
ee	3" x 3/4" x 11/16" hole curved washer				
ff	6" - guy clamp w/3-1/2" bolts				
gg	medium size strain insulator	6454			
hh	receiving sleeve for 3/8" guy strand	7887			X
jj	3/16" x 2-1/2" x 7" lift plate				
mm	pole bottom ground plate (may use butt-wrap if desired)				
qq	Ground Connection (See DWG. ES-12)				
rr	wet process porcelain secondary spool insulator, 3" - white glaze				
tt	wet process porcelain secondary spool insulator, 4" - white glaze				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO HOBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: ELEC SPECS	DRAWING NO: ES-1
		SHEET 5 OF 5	