

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)		DRIFFT ID	OD	WT PER FT	GRADE	THREAD	AMT	WT. IN AIR, WT. IN MUD		REMARKS
FROM-TO	INTERVAL (FT)							1000 LBS	1000 LBS	
(S) 0'-1300'		7.972"	8-5/8"	24#	K-55	STC	1300'	31.2		
(P) 0'-3800'		4.825"	5-1/2"	15.5#	K-55	STC	3800'	58.9		Sandblast bottom 400'

TYPE OF STRING	CENTRALIZERS		SCRATCHER		OTHER ACCESSORY EQUIPMENT		REMARKS
	NO.	INTERVAL	NO.	INTERVAL	(SUCH AS DEGRASSERS, MUD, CENTRIFUGE	FLOAT COLLARS, ETC. - SPECIFY)	
Surface	(13)	0'-1300'	NONE		Guide shoe, float collar		100' spacing for centralizers
Production	(2)	1200'-1300'	(27)	3400'-3800'	Float shoe and float collar		2 centralizers just above 8-5/8" shoe and remainder one every joint.
	(23)	2900'-3800'			if necessary for water flow, use D.V. tool and E.C.P.		15' spacing for scratchers