

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)		WT PER FT		WT. IN AIR, WT. IN MUD		WT. IN AIR, WT. IN MUD		REMARKS
FROM-TO	OD	DRIFT ID	WT PER FT	GRADE	THREAD	AMT	1000 LBS	
(S) 0'-1350'	8-5/8"	7.972"	24#	K-55	STC	1350'	32.4	
(P) 0'-3800'	5-1/2"	4.825"	15.5#	K-55	STC	3800'	58.9	Sandblast bottom 400'

TYPE OF STRING	CENTRALIZERS		SCRATCHER		OTHER ACCESSORY EQUIPMENT		REMARKS
	INTERVAL	NO. FROM-TO	INTERVAL	NO. FROM-TO	(SUCH AS DEGASSERS, MUD. CENTRIFUGE	FLOAT COLLARS, ETC. - SPECIFY)	
Surface	(14) 0'-1350' 100' Spacing	None			Guide shoe and float collar		
Production	(2) 1250'-1350' Just above 8-5/8" shoe (23) 2900'-3800' One per joint	(27) 3400'-3800'	15' Spacing		Float shoe, float collar, and if necessary for water flow, use D.V. Tool & ECP.		