

LIST TYPE OF STRING BY CODE LETTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)	FROM-TO	OD	DRIFT ID	WT PER FT	GRADE	THREAD	AMT	WT. IN AIR, WT. IN MUD		REMARKS
								1000 LBS	1000 LBS	
(S) 0'-1400'		13-3/8"	12.459"	54.5#	K-55	STC	1400'	76.3		
(I) 0'-2600'		8-5/8"	7.796"	32#	K-55	STC	2600'	83.2		D.V. Tool @ 1400'
(P) 0'-6200'		5-1/2"	4.825"	15.5#	K-55	LTC	6200'	96.1		Sandblast bottom 400 D.V. Tool @ 4000'

TYPE OF STRING	CENTRALIZERS		SCRATCHER		OTHER ACCESSORY EQUIPMENT (SUCH AS DEGASSERS, MUD. CENTRIFUGE FLOAT COLLARS, ETC. - SPECIFY)		REMARKS
	INTERVAL		NO. INTERVAL				
	NO. FROM-TO		NO. FROM-TO				
Surface	(14)	0'-1400'	(15' Spacing)	NONE	Guide shoe and float collar	100' spacing for centralizers	
Intermediate	(2)	1300'-1400'		NONE	Float shoe, float collar, ECP, and D. V. Tool @ 1400'	Centralizers: 2 just above 13-3/8" shoe, remainder every other joint.	
	(15)	1400'-2600'					
Production	(2)	2500'-2600'	(27)	5800'-6200'	Float shoe, float collar, and D.V. Tool @ 4000'	Centralizers: 2 just above 8-5/8" shoe, remainder every joint	
	(10)	5800'-6200'					

NOTE: Intermediate will be run only if water is encountered.