

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER REFS. NO.	NO. SHE.
A	35' class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	High density wet process porcelain pin insulator				
D	5/8" x 5" forged steel pin w/eq. washer, nut, & locknut	881	663		
E	3/8" x 12" machine bolt w/ nut (or length req'd)	881/2			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole eq. washer	681/3			
G	3/8" NF locknut	351/2			
H	1/4" x 1 1/4" x 28" flat crossarm brace	712/8			
I	1/2" x 4" E2 Rafter Drive Log Screw	508754			
J	3/8" x 4 1/2" Carriage bolt w/ Nut	8814/1			
K	3/8" NF locknut	351/0			
L	Preformed Aluminum Alloy Armor Rods, size req'd				
M	tie wire #6 strong alum. alloy				
N	Epoxy Insulator (Extension Link)				
O	35' class 5 creosoted pine pole				
P	Aluminum double tab Squeeze on Connector for ACSB, Aluminum, or Copper-size req'd	66200			
R	6" Suspension Insulator	6502			
S	5/8" Standard Oval Eye Nut				
T	Extremity Dead End Clamp	8848	44050		
U	5/8" x 18" (or length req'd) Double Arming Bolt w/6 eq. nuts				
V	Buying detail - see dwg No. ES-10 for specs.				
Y	Hot Line Clamp	5/52026P			
Z	Squeeze on basket, size required				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO PRODUCTION DEPT. HOBBS DIVISION DRAWING NO. ES-1 SHEET 1 OF 3	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: ELEC SPECS	