

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	FLXXIO/G			X
AB	General Purpose up bolt clamp	UC310AGP			
AC	Lightening arrester, 10 KV				
AD	Single phase oil switch, 14.4 KV				
AE	split bolt connector, size req'd				
AF	Rounding spec. see dwg No. ES-11 & ES-1A, Note 3				
AG	351 class 4 creosoted pine pole				
AH	Aluminum deadend preforms for ACSR, size req'd				
AI	30' class 6 creosoted pine pole				
AK	OVERHEAD GRN, #4 ACSR - If Req'd - Ref. Dwg ES-11, ES-1A - Note 3				
AL	Ground connector, motor				
AM	600 V. secondary lightning arrester single phase				
AN	Greenfield type FP liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
AO	req'd size lb fitting, 6 cover, 6 gasket				
AP	transformer tank rounding terminal				
AQ	Bird Guards (insulating boots on transformer bushings)	CW3-15			

DATE: 12-27-71		TITLE: DESCRIPTION MATERIAL	
DRAWN BY: E. WINTER		CONOCO PRODUCTION DEPT. HOBBS DIVISIO DRAWING NO. ES-1 SHEET 2 OF 3	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		FILE SPECS	