

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOBLIN NO.	OTHER MFRS. NO.	NO. SUB.
a	double upset bolt s/aq. nut, round washer, and cotter key on short end, sq. nut and wp locknut on long end, 15 1/8" long (for length required.) wet process porcelain secondary spool insulator, 3" brown plate	7B2B	4101		
b	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES-1B Note: provide clamp and ground conduit parallel groove clamp, size req'd			BURNBY SERIES "UC"	
c	secondary insulator clevis for 4" insulator				
d	5/8" thimblye nut	6510			
e	5/8" x 12" (or length req'd) straight thimblye bolt w/aq. nut	5512			
f	transformer cluster mount bracket (small)			ALUMATOSH LM3-6	X
g	transformer cluster mount bracket (large)			ALUMATOSH LM3-6	X
h	req'd size raintight disconnect & fuses, 3-phase, 600 V, Ref. Dwg No. ES-1B				
i	1" cross plate anchor (or size req'd)	X-16			
j	8-way expanding anchor (size req'd)	BB135			
k	4" brown plate wet process porcelain secondary spool insulator		JO101		
l	5/8" x 7" thimblye anchor rod w/nut (use twineye if req'd - Chance No. 5347)	5317 (AUT 55006P)			
m	3/8" high strength guy strand (10,800 lb.)				
n	preformed guy grip for 3/8" guy strand	5010			
o	3" x 3 1/4" x 11 1/16" hole curved washer	6B23 1/2			X
p	6" - guy clamp w/3-1/2" bolts				
q	medium size strain insulator				
r	serving sleeve for 3/8" guy strand	6454			
s	3/16" x 2-1/2" x 7" lite plate	7887			X
t	pole bottom ground plate (may use butt-wrapp if desired)				
u	Ground connection (See Dwg. ES-12)				
v	wet process porcelain secondary spool insulator, 3" - white plate				
w	wet process porcelain secondary spool insulator, 4" - white plate				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO HOBBS DIVISION DRAWING NO. ES-1 SHEET 5 OF 5	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:		JOB:	
SCALE: NONE		FILED SPECS	