

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other P&A2. NAME OF OPERATOR
CONOCO INC.3. ADDRESS OF OPERATOR
P. O. Box 469, Hobbs, N.M. 88240.4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1750' FNL & 710' FEL
AT TOP PROD. INTERVAL: 611
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

NM 2511

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

SEMU

8. FARM OR LEASE NAME

SEMU EUMONT

9. WELL NO.

118

10. FIELD OR WILDCAT NAME

EUMONT QUEEN GAS

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

7 T-20S, R-37E

12. COUNTY OR PARISH

LEA

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well P&A'd as follows: Spotted 80 sx. class C cmt. w/ red dye on top of radio-active tool @ 3664'. TDC @ 3579'. Had 85' cmt. plug on top of fish. Spotted 200' (80 sx) class C cmt. w/ red dye. Pumped in 80 sx cmt. (class 'C') cmt. Tagged cmt. @ 3265'. Pumped in 100 sx. class 'C' cmt. Tagged cmt. @ 3124'. Tried to whipstock around tool. Drilled to 3310'. Pumped in 320 sx. class C neat @ 3300' - 2629'. Dumped in pea gravel - filled to 2530'. Pumped in 400 sx. Barite w/ 6580. Tagged Barite plug @ 2500'. Dumped in pea gravel - tagged up @ 2520'. Pumped in 1500 sx. class H cmt. & 150 sx. class C w/ cal-seal. Circ. 1505x. to surface TDC @ 303'. Filled hole w/ 30 sx. cmt. Erected P&A marker.

Cleaned location. Steel plaque to be erected after SEMU Eumont #118 is drilled.
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Butler, Jr.TITLE Administrative Supervisor

DATE

8/19/80

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:NMFA-4
4565-5
FILE

TITLE

S. GEOLOGICAL SURVEY

DATE