

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED
DEC 23 1980

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
Amoco Production Company U. S. GEOLOGICAL SURVEY
3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 1980' FWL, Sec. 35
AT TOP PROD. INTERVAL: (Unit C, NE/4, NW/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM-11970

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal BG

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Und. Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
35-22-33

12. COUNTY OR PARISH
Lea

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3526.4 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spotted 100' cement plug using Class H cement with additives from 14630' to 14530'. Spotted 200' cement plug using Class H cement with additives from 13850' to 13650'. Spotted 100' cement plug using Class H cement with additives from 13000' to 12900'. Drilled and washed bridges and stringers from 6166' to 12975'. Acidized with 5000 gal. 15% HCL acid. Currently swab testing.

0+4-USGS, H 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou
1-EI Paso 1-Supron 1-Beard

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Benton Green TITLE Ast. Adm. Analyst DATE 12-19-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

