

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 890' FNL & 2245' FWL, Sec. 10  
AT TOP PROD. INTERVAL: (Unit C, NE 1/4, NW 1/4)  
AT TOTAL DEPTH: 1980' NW

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM-11970

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Federal BG

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Und. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
35-22-33

12. COUNTY OR PARISH  
Lea

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3526.4 GL

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

RECEIVED  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to a TD of 5088' and ran 10-3/4" casing set at 5088'. Cemented with 4500 SX Lite cement with additives and with 200 SX Class C Neat Cement. Plugged down at 7:15 p.m. 8-19-80. Circulated 475 SX. WOC 18 hr. Tested casing with 1500#. Test OK. Reduced hole to 9-1/2" and resumed Drilling.

0+4-USGS, H 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bob Laws TITLE Admin. Analyst DATE 8-27-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 2 1980

U. S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO