

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

C - CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
L-4780	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐		7. Unit Agreement Name
1. Name of Operator Pogo Producing Company		8. Farm or Lease Name NBR
2. Address of Operator P.O. Box 10340 Midland, Texas 79702		9. Well No. 1
3. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 18 TOWNSHIP 22-S RANGE 33-E NMPM.		10. Field and Pool, or Wildcat Wildcat
11. Elevation (Show whether DF, RT, GR, etc.) 3631.2 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1/13/81: TD 15372'. Ran 84 jts (3338.80') 5" 18# S-95 SFJ casing. Shoe @ 15120', FC @ 15076', top of liner @ 11768'. HOWCO cemented w/100 sxs 75/25 Pozmix H (14.3 ppg) w/0.75% CFR-2, 0.4% Halad 22A and 0.4% HR-7 followed w/480 sxs Cl H (15.9 ppg) w/0.6% Halad 22A, 0.4% CFR-2, 5# KCL, 0.5% HR-12 and 0.37#/sk gas-chek. Pump plug w/140 bbls (3 bbls over), did not bump plug. CIP @ 11:15 pm 1/12/81.
- 1/14/81: TD 15372'. WOC 12 hrs. RIH w/6 1/2" mill. TOC in 7 3/4" @ 11759'. Clean out hard cement from 11759'-11768'. Circ clean. POH. RIH w/4 1/8" mill & 2 7/8" tubing.
- 1/15/81: TD 15372'. RIH to TOL, CO 1 1/2' cement in liner top. RIH to 12713'. Drld cement 12713'-13337' (624'). MW 12.8, Vis 48, CL 95,000.
- 1/16/81: TD 15372'. Drl cement 13337'-13400' (63'), trip for new mill. MW 14.4, Vis 56, CL 100,000.
- 1/17/81: TD 15372'. Drl cement 13400'-13790' (390') MW 12.4, Vis 52, CL 100,000.
- 1/18/81: TD 15372'. Drl cement to 14069' (279') MW 12.5, Vis 50, CL 100,000.
- 1/19/81: TD 15372'. Drl cement to 14355' (286') MW 11.8, Vis 46, CL 100,000.
- 1/20/81: TD 15372'. Drl cement to 14865' (510') MW 11.6, Vis 42, CL 110,000.
- 1/21/81: PSTD 15060'. Drl cement to 15060' (195') MW 12.1, Vis 51, CL 110,000.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>B. Williams</u>	TITLE <u>Division Operations Manager</u>	DATE <u>January 28, 1981</u>
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		

FEB 2 1981