

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P.O. Box 460, Hobbs, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1750' FNL & 710' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Set prod. csg.

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE

NM 2511

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

SEMU

8. FARM OR LEASE NAME

SEMU Eumont

9. WELL NO.

1184

10. FIELD OR WILDCAT NAME

Eumont Queen Gas

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 27, T-20S, R-37E

12. COUNTY OR PARISH

LEA

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-331.)
SEP 09 1980U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Reached TD of 3770' on 9-1-80. Ran 5 1/2", 15.5# csg. Tagged up @ 3760'. Ran free-point - csg. stuck @ 3400', free @ 3465'. Guide shoe set @ 3741'. DV tool @ 1102'. Drilled out DV tool & set C/BP @ 3638'-3641'. Perf. @ 3520'-21' w/ 4 shots. Set pkr. @ 3567'. Perf. @ 3460'-61' w/ 4 shots. Set pkr. @ 3410'. Set amt. retainer @ 3405'. Empd. in 1100 sx. class "C" cnt. w/ additives. Tailed in w/ 350 sx. class "C" cnt. Circ. 215 SX-cnt. to surface

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. A. ButlerTITLE Admin. Supervisor

DATE

9-5-80

(This space for Federal or State office use)

ACCEPTED FOR RECORD

J. Chester

DATE

SEP 15 1980

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

USGS-5
NMFU-4
FILE