

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP DATE
(Other instruction
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME Warren Unit
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME Warren Unit
3. ADDRESS OF OPERATOR PO Box 460, Hobbs, NM 88240	9. WELL NO. 86
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL + 890' FEL Unit I	10. FIELD AND POOL, OR WILDCAT Blinebry / Warren Tubb
14. PERMIT NO. 30-025-27092	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29-205-38E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3527.1' GR	12. COUNTY OR PARISH Lea
	13. STATE Nm

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>

(Other) Downhole Commingle ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. POOH w/tbg.
2. Remove retrievable bridge plug.
3. Acidize Blinebry + Tubb w/50 bbls each 75% 15% HCL
25% Xylene.
4. Run tbg.
5. Run rods.
6. Place well on production.

RECEIVED
JUL 6 10 35 AM '88
CARLSBAD OFFICE
AREA ENGINEERS

18. I hereby certify that the foregoing is true and correct

SIGNED D. F. Finney
(This space for Federal or State office use)

TITLE Administrative Supervisor

DATE 7/5/88

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE 7-18-88

*See Instructions on Reverse Side