

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
---	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
Name of Operator		---
MORRIS R. ANTWEIL		8. Farm or Lease Name
Address of Operator		Roberts
P. O. Box 2010 Hobbs, New Mexico 88240		9. Well No.
1		10. Field and Pool, or Wildcat
Location of Well		Undesignated
UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM		
THE East LINE, SECTION 5 TOWNSHIP 20-S RANGE 38-E NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3582' GR		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well @ 8:45 AM 7 December 80. Drilled 12 1/4" hole to 1500'. Ran 39 jts. 8 5/8" 24# H-40 casing & cemented @ 1500' w/450 sx Halliburton Lite cement containing 5 #/sx gilsonite, 1/4 #/sx Flocele & 2% CaCl<sub>2</sub> and 300 sx Class C cement containing 2% CaCl<sub>2</sub>. Plug down 6:40 AM 9 December 80. Circulated 100 sx. WOC 18 hrs. Tested casing w/2000 psi - 30 mins. - OK. Drilled out & drilling ahead w/7 7/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rm Williams TITLE Agent DATE 10 Dec 80

APPROVED BY Only Signed By TITLE  DATE DEC 11 1980  
CONDITIONS OF APPROVAL, IF ANY: