## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

MO. OF COPIES ACCEIVES		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.	1	
LAND OFFICE		
OPERATOR		

CONDITIONS OF APPROVAL, IF ANYI

## OIL CONSERVATION DIVISION

Form C-103

DISTRIBUTION	Р. О. ВОХ	( 2088	Revised 10-1-3
SANTA FE	SANTA FE, NEW	MEXICO 87501	
FILE	•		5a. Indicate Type of Lease
U.S.O.S.			State Fee X
LAND OFFICE			5. State Oil & Gas Lease No.
OPERATOR			
	THE PERSON OF TH	WELLS	
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			
USC "APPLICATIO	OH FOR PERMIT -" (FORM C-101) FOR SUCH	( PROPOSALE.)	7. Unit Agreement Name
:. OLL [32] GAS [7]			
WELL X	OTHER-		8. Farm or Lease Name
Name of Operator ,		Eggbert	
MORRIS R. A	ANTWEIL		
. Address of Operator			9, Well No.
Box 2010 Hobbs, New Mexico 88240		1	
ocation of Well		10. Field and Pool, or Wildcat	
UNIT LETTER H . 1980 FEET FROM THE NORTH LINE AND 660 FEET FR		Undesignated	
UNIT LETTER H	1980' FEET FROM THE NOTED	LINE AND DOU FEET FRO	THITTINING "
THE East LINE, SECTION 8 TOWNSHIP 20-S RANGE 38-E NMPI			
			<del>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</del>
	15. Elevation (Show whether	DF, RT, GR, etc.)	Lea (12. County
	3565' GR		Tea VIIIIII
16. Charles	Appropriate Box To Indicate N	ature of Notice Report of O	ther Data
		SUBSECULE	NT REPORT OF:
NOTICE OF IN	TENTION TO:	308324021	THE ONLY
-			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	
7000 04 40100 00000		OTHER	
		,	
OTHER			
? Describe Proposed or Completed Op	erations (Clearly state all pertinent deta	ails, and give pertinent dates, includir	ng estimated date of starting any proposed
work) SEE RULE 1103.			
		D : 11 1 10 1//U 1	1-1- 4- 15001
Spudded we	11 7:30 AM 26 Feb 81	. Drilled 12 1/4"	note to 1000.
Ran 39 jts	. 8 5/8" 24# J-55 ca	sing and cemented at	E 1500, MICU
450 sx Hal	liburton Lite cement	containing 5 #/sx {	gilsonite,
1/4 #/sx F	locele and 2% $CaCl_2$	and 300 sx Class "C"	" cement con-
taining 2%	CaCl2. Plug down @	6:30 PM 27 Feb 81.	Circulated
75 sy ceme	nt. WOC 18 hrs. Te	sted casing with 150	00 psi -
75 54 CCMC	OK. Drilled out & d	rilling ahead w/7 7	/8" bit.
- Shirm DC	OR. DITTIER OUT & C	riffing andad with the	, • 222
	•		•
	•		
		of my knowledge and belief.	
18. I hereby certify that the information	above is true and complete to the best	AS 10.5 DESCRIPTION OF THE OWNERS.	
	•	A = 0 = +	17 Mar 81
116480 Cmwillian	YITLE	Agent	DATE
>10000			

RECEIVED

MAR 1 9 1981

ULU CUNSERVATION DIV