

DATE: 12-05-88

WELL NO. & TYPE OF JOB: State 731 # 1: P&A

DRILLED: \_\_\_\_\_ LAST WO: Acidized 1987 No Response

FIELD: Jalmat COUNTY: Lea Co., NM BY: M.W. Gore

TD: 3983' PBD: 3898' DATUM: RKB DIST RKB TO THF: ?

CASING INFORMATION:	SIZE	WEIGHT	GRADE	SET @	SX CMT	TOC
SURFACE:	<u>8-5/8"</u>	<u>24.0</u>	<u>J-55</u>	<u>1754</u>	<u>1000</u>	<u>Surface</u>
INTERMEDIATE:						
PRODUCTION:	<u>5-1/2"</u>	<u>15.5#</u>	<u>K-55</u>	<u>3983</u>	<u>600</u>	<u>Surface</u>
LINER:						

PRESENT PERFORATIONS: 3768-3878'

TUBING DATA: SIZE ? WT. \_\_\_\_\_ GRADE \_\_\_\_\_ THD. \_\_\_\_\_ BTMD @ \_\_\_\_\_  
NO. OF JTS. \_\_\_\_\_ MISC. \_\_\_\_\_

PACKER & MISC.: \_\_\_\_\_

#### PROCEDURE

1. MIRU PU. NU BOP. Pull and LD rods. POOH w/ tubing.
2. Set CIBP @ 3720 and dump bail 35' cement on CIBP.
3. GIH w/ tubing to 3650' and circulate hole w/ 10 ppg gelled BW.
4. POOH to 1804 and spot a 50 sack Class "C" cement plug.
5. POOH and cement surface w/ 10 sacks.
6. ND BOPE and cut off wellhead and install dry hole marker.

RECEIVED

DEC 16 1988

OCD  
HOBBS OFFICE