

DATE: 01-26-⁸⁹~~88~~

WELL NO. & TYPE OF JOB: State 731 # 2: P&A

DRILLED: 1981 LAST WO: _____

FIELD: Jalmat COUNTY: Lea Co., NM BY: M.W. Gore

TD: 3997' PBD: 3948' DATUM: RKB DIST RKB TO THF: ?

CASING INFORMATION:	SIZE	WEIGHT	GRADE	SET @	SX CMT	TOC
SURFACE:	<u>8-5/8"</u>	<u>24.0</u>	<u>J-55</u>	<u>1751</u>	<u>1000</u>	<u>Surface</u>
INTERMEDIATE:						
PRODUCTION:	<u>5-1/2"</u>	<u>15.5#</u>	<u>K-55</u>	<u>3997</u>	<u>600</u>	<u>Surface</u>
LINER:						
PRESENT PERFORATIONS: <u>3788-3900'</u>						

TUBING DATA: SIZE 2-3/8 WT. 4.7 GRADE J-55 THD. _____ BTMD @ 3925
NO. OF JTS. 127 MISC. _____

PACKER & MISC.: _____

PROCEDURE

1. MIRU PU. NU BOP. Pull and LD rods. POOH w/ tubing.
2. Run CIBP on tubing and set same @ 3750'. TEST CASING to 500'
3. Circulate hole w/ 10 ppg gelled BW and spot 10 sack plug at 3750'.
4. POOH to 1800' and spot a 50 sack Class "C" cement plug.
5. POOH and cement surface w/ 10 sacks.
6. ND BOPE and cut off wellhead and install dry hole marker.

Approved: K. D. Krawietz *KDK 1/26/89*
D. R. McKelvey *DM 1/26/89*
G. D. Kimbrough
B. N. Brown