

DISTRIBUTION

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-85

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil &amp; Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator  
Tamarack Petroleum Co., Inc.

3. Address of Operator  
500 W. Texas, Suite 1485, Midland, TX 79701

4. Location of Well  
UNIT LETTER G 1780 FEET FROM THE North LINE AND 2080 FEET FROM  
THE east LINE, SECTION 8 TOWNSHIP 20-S RANGE 38-E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name  
Patterson

9. Well No.  
1

10. Field and Pool, or Wildcat  
W. Nadine Blinbry

15. Elevation (Show whether DF, RT, GR, etc.)  
3565.7 GR

12. County  
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☒  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 5/28/86 Move in and rig up pulling unit. Pull out of hole with rods and pump. Nipple up BOPE and pull out of hole with tubing.
- Run in hole with Western retrievable bridge plug. Set at 5961' and tested. Spot 250 gals 15% HCL at 5929'.
- 5/29/86 Rig up CRC Wireline and perforated with 16 casing jets from 5924' to 5929'. Run in hole with Baker Model "R" double grip packer and set at 5873'.
- 5/30/86 acidized with 2250 gals 15% dolowash acid and balled out. Swab back spent acid water.
- 5/31/86 pull out of hole with packer. Run in hole with production tubing, rods and pump. Set pump seating nipple at 5824'. Start well pumping.
- 6/5/86 well pumping 42 barrels oil and 5 barrels water.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Randy A. McClary

TITLE Engineering Manager

DATE 6/11/86

Eddie W. Seay

APPROVED BY Oil & Gas Inspector

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 1 1986

RECEIVED  
JUL 12 1966  
STATE OF OHIO  
DEPT. OF REVENUE