

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-7

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Burnett Oil Co., Inc.	8. Farm or Lease Name Caroline Dewey
3. Address of Operator 1214 First Natl. Bank Bldg., Ft. Worth, Texas 76102	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>East</u> LINE AND <u>660</u> FEET FROM THE <u>North</u> LINE, SECTION <u>24</u> TOWNSHIP <u>20S</u> RANGE <u>38E</u> N.M.P.M.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3563' G1	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
		OTHER <u>Spud &amp; set surface casing</u>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well spudded at 3:30 p.m. 8-8-81. Set 1638' of 8 5/8" 24# J-55 casing & cemented with 550 sx. Class "C" cement, 4% gel, 2% CaCl, 1/4# flocele/sk & 300 sx. Class "C", 2% CaCl, 1/4# flocele/sk. Tested to 1000 psi, held okay.  
Drilled ahead with no problems.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John C. McPhaul TITLE John C. McPhaul Production Supt. DATE 3-3-82

APPROVED BY OFFICIAL SIGNED BY TITLE APPROVED BY DATE APR 13 1982  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 15 1982

O.C.D.  
HOBBS OFFICE