

6-USGS-Roswell  
1-Drlg. Foreman-OH

1-File  
1-Engr.-DW  
7-WIO's  
NOBBS, NEW MEXICO 88240

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
Getty Oil Company

3. ADDRESS OF OPERATOR  
P.O. Box 730 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Unit ltr. C, 1980' FWL & 660' FNL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Run liner

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
NM-14332

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Bilbrey Fed. Com.

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 4, T-22S, R-32E

12. COUNTY OR PARISH  
Lea

13. STATE  
NM

14. API NO.  
3791.9 GR

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11/13/81 Drilled 6 1/8" hole to 15,105'. Ran 62 jts. (2447.61') 4 1/2" OD 8rd 13.5# S-95 LT&C R-3 casing and set @ 15,100' (Top Liner @ 12,620'), Howco cemented w/15 bbls Sam 4, 100 sxs. Poz Mix A w/.75% CFR-2Sk, .4% Halad - 22/sk, .4% HR-5 and tailed in w/300 sxs. Class "H" cement w/.6% Halad 22-A, .5% CFR-2, .4% HR-5, 3# KCl/sk, gas check - followed w/15 bbl Sam 4, 15 bbls. mud, 5 bbls. Sam 4 and bumped plug w/83 bbls. mud @ 2000# @ 11:15 A.M. WOC.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE

Area Superintendent

DATE

November 23, 1981

APPROVED BY  
CONDITIONS OF

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE

DATE