		N. M. 8		CONVERSION			
6 USGS-ROSWELL 1 DRLG. FOREMAN-OH	1 FILE 1 ENGRDW	P. O. E HOBBS	IOX 1 5, NE	1930 W MEXICO 6824	0		
Form 9-331 Dec. 1973	7 WIO'S				Approved. et Bureau No. 42-R1424		
UNITED		5.	LEASE				
DEPARTMENT OF THE INTERIOR			NM-14332				
GEOLOGICAL	SURVEY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
SUNDRY NOTICES AND			7.	UNIT AGREEMENT N	AME		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)		8.	FARM OR LEASE NAM	ENAME			
1. oil gas y				Bilbrey Fee	d. Com.		
well well X other				WELL NO.			
2. NAME OF OPERATOR				1			
Getty Oil Company			10.	FIELD OR WILDCAT I	NAME		
3. ADDRESS OF OPERATOR		-					
P.O. Box 730 Hobbs, New Mexico 88240			11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit Ltr. C, 1980' FWL & 660'					r-22s, R-32E		
below.) Unit Lt: AT SURFACE:		FNL	12.	COUNTY OR PARISH			
AT TOP PROD. INTERVAL:	_			Lea	NM		
AT TOTAL DEPTH:			14.	API NO.	·		
16. CHECK APPROPRIATE BOX TO	INDICATE NATURE OF	NOTICE,					
REPORT, OR OTHER DATA			15.	ELEVATIONS (SHOW	V DF, KDB, AND WD)		
DEQUEST FOR ADDOVAL TO	SUBSEQUENT REPOR			3791.9 GR			
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF	SUBSEQUENT REPOR						
FRACTURE TREAT	। বি দি দি	RET	16/1	สกา	,		
SHOOT OR ACIDIZE		0,000	<u>Mr</u>	2			
REPAIR WELL					ultiple completion or zone		
PULL OR ALTER CASING	H JIN A	UG 28	1981	ionange on Form 9	-330.)		
CHANGE ZONES				d			
ABANDON*	d	CIL & G		5) (S) (
(other)		GEOLOGIC MELL, NEW					
				nartinant dataila and			

....

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 121" hole to 4850', Ran 32 Jts. (1400'). 9 5/8" S-80 36# 8rd Lt&C 8-21-81 and 98 Jts. (3428') K-55, 36#, 8rd LT&C casing and set at 4850'. FC @ 4800'.

8-22-81 How co cemented with 3000 sxs. Lite with 15# salt, $\frac{1}{2}$ # flocele, 5# Gilsonite. Tailed in with 250 sxs. Class "C" cement with 1 Flocele. Total cement 3250 sxs. Circulated 500 sxs. cement.

8-23-81 Waited on cement 24 hrs. Pressured up to 1200# for 30 mins. OK.

ì

Subsurface Safety Valve: Мали. and Туре			Set @		Ft.
18. I hereby certify that the foregoing is true SIGNED	and correct	DATE	August 26,	1981	
	his space for Federal or State office use)	DATE .			
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO	*See Instructions on Reverse Side				