

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OCD - 0 + 2
FILE 1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
NM-1248

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Foran Oil Company 3. Address of Operator C/O Unique Engineering, Inc. P.O. Box 5970 Hobbs, New Mexico 88241 4. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 6 TOWNSHIP 22S RANGE 33E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3659.2 GL	7. Unit Agreement Name 8. Farm or Lease Name San Simon State Com 9. Well No. 1 10. Field and Pool, or WHdcat Wildcat 12. County Lea
--	---

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL TO ALTER CASING <input type="checkbox"/>	OTHER PB and test the Delaware pay <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

June 1, 1988 - Estimated date of starting re-completion

Rig up workover rig.
Pull rods and pump.
Install BOP
Set RBP at approximately 5100'.
Load hole w/ RC/water
Run CBL/CET
If good cement, perforate 2SPF as follows: 4921', 25', 31', 34', 36' and 40'.
Spot acid across perfs.
Acidize w/ 1000 gal. 7½%.
Swab test
If necessary frac.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Consulting Engineer DATE 5-19-88

ORIGINAL SIGNED BY JERRY SEXTON
APPROVED BY DISTRICT 1 SUPERVISOR TITLE DATE MAY 24 1988
CONDITIONS OF APPROVAL, IF ANY: