

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
--	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator		8. Farm or Lease Name	
MORRIS R. ANTWEIL		HUEY	
3. Address of Operator		9. Well No.	
P. O. Box 2010, Hobbs, NM 88240		2	
4. Location of Well		10. Field and Pool, or Whdcat	
UNIT LETTER F, 2310 FEET FROM THE North LINE AND 1980 FEET FROM		Undesignated	
THE West LINE, SECTION 5 TOWNSHIP 20-S RANGE 38-E NMPM.			
15. Elevation (Show whether DF, RT, GR, etc.)		12. County	
3582' GR		Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 7150' TD. Ran logs. Ran 169 jts 5½" 17# J-55 casing & cemented at 7150' with 365 sx Halliburton light cement with 18% salt and ¼#/sk flocele and 300 sx Class "C" cement with 5#/sk salt and ¼#/sk flocele. Plug down 11:45 AM 22 April 82. After 6 hours WOC, Temperature Survey shows TOC at 3370'. PBTD 7110'. Will test casing when completion operations begin.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Hillard TITLE Agent DATE 26 April 82

APPROVED BY ORIGINA TITLE APR 28 1982

CONDITIONS OF APPROVAL, IF ANY: