

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	For <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
--	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
MORRIS R. ANTWEIL	LOUIE
3. Address of Operator	9. Well No.
P. O. Box 2010, Hobbs, NM 88240	2
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER <u>L</u> , 1980 FEET FROM THE <u>South</u> LINE AND <u>860</u> FEET FROM	West Nadine Drinkard
THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>20-S</u> RANGE <u>38-E</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3583' GR	Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 7150'. Reached TD at 5 PM 30 May 82. Ran logs. Ran 178 jts 5½" 15.5# & 17# casing and cemented at 7150' with 375 sx Halliburton Light cement with 18% salt and ¼#/sk flocele and 300 sx Class "C" with 5#/sk salt & ¼#/sk flocele. Plug down 1 PM 2 June 82. After 6 hrs WOC, Temperature Survey shows TOC at 3500'. PBTD 7110'. Will test casing when completion operations begin.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Hill TITLE Agent DATE 4 June 82

APPROVED BY JERRY HILL TITLE DATE JUN 7 1982

CONDITIONS OF APPROVAL, IF ANY: