

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5. State Oil & Gas Lease No.
2. Name of Operator Crown Central Petroleum Corporation		7. Unit Agreement Name
3. Address of Operator 731 W. Wadley, Bldg. K, Suite 200, Midland, Texas 79701		8. Farm or Lease Name McCallister
4. Location of Well UNIT LETTER <u>C</u> <u>660</u> FEET FROM THE <u>N</u> LINE AND <u>1980</u> FEET FROM THE <u>W</u> LINE, SECTION <u>8</u> TOWNSHIP <u>20S</u> RANGE <u>38E</u> NMPM.		9. Well No. 3
15. Elevation (Show whether DF, RT, GR, etc.) 3569 GL		10. Field and Pool, or Wildcat West Nadine- Driskard
		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER _____ <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER _____ <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1564'. Running 1560' of 8 5/8" 24# J-55. Ran guide shoe, float collar and 4 centralizers. Set 1528' of casing cemented with 300 sx with 4% gel, 1/4#/sx flocele + 300 sx with 15#/sx Gilsonite, 1/4# Flocele. Ran temperature survey, found cement top at 292'. Spotted 150 sx Class C, 3% CaCl, 1% friction reducer, 1/4#/sx flocele. Cement did not come to surface, gravel packed with 7 1/2 yds. pea gravel and cemented with 5 yds. of redi-mix cement. Drilled out and tested to 500#.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED K.K. Kirby K.K. Kirby TITLE Petroleum Engineer DATE December 14, 1982

APPROVED BY JERRY SEXTON /
 CONDITIONS OF APPROVAL, IF ANY DISTRICT 1 SUPR.

TITLE _____ DATE DEC 27 1982

RECEIVED
DEC 16 1982
O.C.D.
HOSES OFFICE