

HERMAN #4

Proposed Remedial Work

1. MIRU PU. Pull rods & tbg. Run csg collar log.
2. Perf Blinebry Zone fr/6,282'-6,312' (6 holes).
3. Acidize under pkr new & existing perfs fr/6,282'-6,437' w/1,800 gals 15% NEFE HCl acid w/ball sealers.
4. Frac under pkr new & existing perfs fr/6,282'-6,437' w/29,000 gals x-linked gel carrying 75,000# 20/40 Ottawa sd.
5. Perforate Blinebry Zone fr/6,079'-6,103' (6 holes).
6. Set RBP @ 6,200'. Acidize under pkr new perfs fr/6,079'-6,103' w/1,000 gals 15% NEFE HCL acid w/ball sealers.
7. Frac under pkr new & existinig perfs fr/5,988'-6,103' w/21,000 gals x-linked gel carrying 50,000# 20/40 Ottawa sand.
8. Perforate additional Blinebry fr/5,826'-5,910' (10 holes).
9. Set RBP @ 5,950'. Acidize under pkr new perfs fr/5,826'-5,910' w/1,500 gals 15% anti-sludge HCL acid w/ball sealers.
10. Pull RBP's & clean out frac sd fill.
11. Run tbg & rods. RDMO pulling unit. Rtn'd to ppg old & new Blinebry perfs and old Tubb perfs.