

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Sun Exploration & Production Co. 3. Address of Operator P. O. Box 1861 Midland, TX 79701 4. Location of Well UNIT LETTER E 2570 FEET FROM THE North LINE AND 70 FEET FROM West LINE, SECTION 9 TOWNSHIP 22-S RANGE 36-E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3585.0' GR	7. Unit Agreement Name 8. Farm or Lease Name State "A" A/C 2 9. Well No. 68 10. Field and Pool, or Wildcat Eunice Seven Rivers Queen South 12. County LEA
---	---

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input checked="" type="checkbox"/> Convert to WIW	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) MIRU. POH w/rods & pump. Install BOP. Lower tbg to PBTD 3880 to check for fill over perfs. POH w/2-3/8 tbg. If fill over perfs, CO to PBTD by circ w/notched collar or hydrostatic bailer on 2-3/8 tbg.
- 2) RIH w/Otis Perma-Lach pkr w/OSTSD and 1.50" "N" profile landing nipple on 2-3/8 cmt lined tbg. Circ and load hole w/pkr fluid. (1 gal Tretolite KW-79 per 100 gals wtr). Set pkr at 3700. Establish inj rate at 1 BPM. RR.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Seay TITLE Associate Accountant DATE 9-4-84

Eddie W. Seay

OCT 10 1984

APPROVED BY Oil & Gas Inspector

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

SEP 5 1984

G. C. B.  
HOBBS OFFICE